## NSN 4820-01-315-6367

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-315-6367

Pipe Size Accommodated:
0.500 inches all ends
Flow Control Device:
Stem
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Connection Style:
Socket all ends
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Maximum Operating Pressure:
4500.0 pounds per square inch single response
Criticality Code Justification:
Zzzy
Special Features:
Welded nipples
Material:
Nickel alloy body
Nickel alloy body  Material Specification:
Material Specification:
Material Specification:  Qq-n-286 federal specification single material response stem
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:  Err-090
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:  Err-090  Furnished Items And Quantity:
Material Specification: Qq-n-286 federal specification single material response stem Style Designator: Err-090 Furnished Items And Quantity: 1 handle
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:  Err-090  Furnished Items And Quantity:  1 handle  Fsc Application Data:
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:  Err-090  Furnished Items And Quantity:  1 handle  Fsc Application Data:  Non prpln plant sys
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:  Err-090  Furnished Items And Quantity:  1 handle  Fsc Application Data:  Non prpln plant sys  Reference Number Differentiating Characteristics:
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:  Err-090  Furnished Items And Quantity:  1 handle  Fsc Application Data:  Non prpln plant sys  Reference Number Differentiating Characteristics:  Quality controlled iaw navy level 1 assurance guide, cleaned iaw mil-c-52211
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:  Err-090  Furnished Items And Quantity: 1 handle  Fsc Application Data:  Non prpln plant sys  Reference Number Differentiating Characteristics:  Quality controlled iaw navy level 1 assurance guide, cleaned iaw mil-c-52211  Shelf Life:
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:  Err-090  Furnished Items And Quantity:  1 handle  Fsc Application Data:  Non prpln plant sys  Reference Number Differentiating Characteristics:  Quality controlled iaw navy level 1 assurance guide, cleaned iaw mil-c-52211  Shelf Life:  N/a
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:  Err-090  Furnished Items And Quantity:  1 handle  Fsc Application Data:  Non prpln plant sys  Reference Number Differentiating Characteristics:  Quality controlled iaw navy level 1 assurance guide, cleaned iaw mil-c-52211  Shelf Life:  N/a
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:  Err-090  Furnished Items And Quantity:  1 handle  Fsc Application Data:  Non prpln plant sys  Reference Number Differentiating Characteristics:  Quality controlled iaw navy level 1 assurance guide, cleaned iaw mil-c-52211  Shelf Life:  N/a  Unit Of Measure:
Material Specification:  Qq-n-286 federal specification single material response stem  Style Designator:  Err-090  Furnished Items And Quantity:  1 handle  Fsc Application Data:  Non prpln plant sys  Reference Number Differentiating Characteristics:  Quality controlled iaw navy level 1 assurance guide, cleaned iaw mil-c-52211  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: