## NSN 4820-01-315-7606

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-315-7606

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
8.000 inches
Adjustable Pressure Range:
+100.0/+300.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
13.500 inches all ends
Thickness:
1.125 inches all ends
First Connection Face To Centerline Distance:
12.750 inches
Bolt Hole Diameter:
0.875 inches all ends
Second Connection Face To Centerline Distance:
8.000 inches
Bolt Circle Diameter:
11.750 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
10.625 inches all ends

## NSN 4820-01-315-7606

Safety Relief Valve - Page 2 of 2



wateriai:
Stainless steel seat
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A046b0