NSN 4820-01-315-7606

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-315-7606

Flow Control Device: Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

8.000 inches

Adjustable Pressure Range:

+100.0/+300.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch single response

Outside Diameter:

13.500 inches all ends

Thickness:

1.125 inches all ends

First Connection Face To Centerline Distance:

12.750 inches

Bolt Hole Diameter:

0.875 inches all ends

Second Connection Face To Centerline Distance:

8.000 inches

Bolt Circle Diameter:

11.750 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

10.625 inches all ends



NSN 4820-01-315-7606

Safety Relief Valve - Page 2 of 2

Material:

Stainless steel seat

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

