# NSN 4820-01-316-1065

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-316-1065



# Flow Control Device:

Disk

Bonnet Type:

Inside screw

# **Bonnet Attachment Method:**

Bolted

# **Bolt Hole Quantity:**

4 all ends

# Maximum Operating Temp:

150.0 degrees fahrenheit single response

# Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

# **Connection Type:**

Flange all ends

Valve Size:

3.000 inches

# Adjustable Pressure Range:

+30.0/+34.0 pounds per square inch

# Maximum Operating Pressure:

250.0 pounds per square inch single response

# **Outside Diameter:**

6.625 inches all ends

#### Thickness:

0.938 inches all ends

# First Connection Face To Centerline Distance:

5.590 inches

# Bolt Hole Diameter:

0.688 inches all ends

# Second Connection Face To Centerline Distance:

6.090 inches

# **Bolt Circle Diameter:**

5.500 inches all ends

# Flange Face Design:

Plain all ends

# Material:

Nickel alloy flow control device

# Style Designator:

Err-090

# Shelf Life:

N/a

# NSN 4820-01-316-1065

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

