

View Online at <https://aerobasegroup.com/nsn/4820-01-316-4569>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Pressure tight outlet side

Valve Size:

3.000 inches

Adjustable Pressure Range:

+59.0/+72.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

6.625 inches all ends

Thickness:

0.500 inches all ends

First Connection Face To Centerline Distance:

5.750 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

5.750 inches

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Stainless steel stem

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Specification Or Standard:

B grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.