NSN 4820-01-316-7364

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-316-7364

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Retaining screw

Maximum Operating Temp:

420.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe 2nd end

Mounting Facility:

Threaded fastener

Adjustable Pressure Range:

+15.0/+350.0 pounds per square inch

Maximum Operating Pressure:

350.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Special Features:

Lifting lever and vented bonnet

Material:

Copper alloy body

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

NSN 4820-01-316-7364

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

