NSN 4820-01-317-2750

Lift-check Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-317-2750

Disk						
Bonnet Type:						
Outside screw-yoke						
Bonnet Attachment Method:						
Bolted						
Bolt Hole Quantity:						
4 all ends						
Maximum Operating Temp:						
366.0 degrees fahrenheit single response						
Valve Operation Method:						
Automatic						
Flange Shape:						
Round with holes all ends						
Connection Type:						
Flange all ends						
Mounting Position:						
Horizontal						
Valve Size:						
1.500 inches						
Maximum Operating Pressure:						
150.0 pounds per square inch single response						
Outside Diameter:						
5.000 inches all ends						
Face To Face Distance:						
6.000 inches						
Thickness:						
0.438 inches all ends						
Bolt Hole Diameter:						
0.625 inches all ends						
Bolt Circle Diameter:						
3.875 inches all ends						
Flange Face Design:						
Plain all ends						
Material:						
Copper alloy body						
Media For Which Designed:						
Steam single response						
Style Designator:						
Straight through flanged ends						
Furnished Items And Quantity:						

1 handwheel

NSN 4820-01-317-2750

Lift-check Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0