NSN 4820-01-317-7429

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-317-7429

Bolted
Bolt Hole Quantity:
8 1st end
Maximum Operating Temp:
450.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Maximum Operating Pressure:
185.0 pounds per square inch single response
Opening Pressure Setting:
70.0 pounds per square inch
Outside Diameter:
9.000 inches 1st end
Thickness:
0.938 inches 1st end
First Connection Face To Centerline Distance:
6.375 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
6.125 inches
Bolt Circle Diameter:
7.500 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
6.188 inches 1st end
Material:
Stainless steel flow control device

NSN 4820-01-317-7429

Safety Relief Valve - Page 2 of 2



М	edia	For	Wh	ich	Desi	aned:
IVI	cuia	1 01	***		DESI	uncu.

Steam single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A046b0