

View Online at <https://aerobasegroup.com/nsn/4820-01-317-7429>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 1st end

Maximum Operating Temp:

450.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

3.000 inches

Maximum Operating Pressure:

185.0 pounds per square inch single response

Opening Pressure Setting:

70.0 pounds per square inch

Outside Diameter:

9.000 inches 1st end

Thickness:

0.938 inches 1st end

First Connection Face To Centerline Distance:

6.375 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

6.125 inches

Bolt Circle Diameter:

7.500 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

6.188 inches 1st end

Material:

Stainless steel flow control device

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0