# NSN 4820-01-319-4332

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-319-4332



## Flow Control Device:

Disk

Bonnet Type:

Inside screw

## **Bonnet Attachment Method:**

Bolted

### **Bolt Hole Quantity:**

4 all ends

### Maximum Operating Temp:

150.0 degrees fahrenheit single response

## Valve Operation Method:

Automatic

Flange Shape:

## Round with holes all ends

## **Connection Type:**

Flange all ends

#### Valve Size:

1.000 inches

#### Adjustable Pressure Range:

+30.0/+34.0 pounds per square inch

#### Maximum Operating Pressure:

150.0 pounds per square inch single response

#### **Outside Diameter:**

4.250 inches all ends

#### Thickness:

0.438 inches all ends

#### First Connection Face To Centerline Distance:

3.314 inches

#### Bolt Hole Diameter:

0.562 inches all ends

#### Second Connection Face To Centerline Distance:

3.314 inches

#### **Bolt Circle Diameter:**

3.125 inches all ends

#### Flange Face Design:

Plain all ends

#### Material:

Nickel alloy flow control device

#### Media For Which Designed:

Water-oil-gas single response

#### Style Designator:

Err-090

# NSN 4820-01-319-4332

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

