

View Online at <https://aerobasegroup.com/nsn/4820-01-320-1223>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Bolt Hole Quantity:

6 1st end

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Pressure tight outlet side

Valve Size:

1.500 inches

Adjustable Pressure Range:

+30.0/+50.0 pounds per square inch

Maximum Operating Pressure:

400.0 pounds per square inch single response

Outside Diameter:

5.062 inches 1st end

Thickness:

0.438 inches all ends

First Connection Face To Centerline Distance:

3.750 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

3.750 inches

Bolt Circle Diameter:

3.375 inches 2nd end

Flange Face Design:

Plain all ends

Material:

Rubber butadiene-acrylonitrile class nbr flow control device

Material Specification:

Qq-n-228 federal specification single material response stem

Media For Which Designed:

Water, salt single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Specification Data:

81349-mil-v-24332 government specification

Specification Or Standard:

B grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.