

View Online at <https://aerobasegroup.com/nsn/4820-01-320-1223>

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Threaded

**Disk Loading Method:**

Spring

**Bolt Hole Quantity:**

6 1st end

**Maximum Operating Temp:**

180.0 degrees fahrenheit single response

**Valve Operation Method:**

Automatic

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Pressure tight outlet side

**Valve Size:**

1.500 inches

**Adjustable Pressure Range:**

+30.0/+50.0 pounds per square inch

**Maximum Operating Pressure:**

400.0 pounds per square inch single response

**Outside Diameter:**

5.062 inches 1st end

**Thickness:**

0.438 inches all ends

**First Connection Face To Centerline Distance:**

3.750 inches

**Bolt Hole Diameter:**

0.562 inches all ends

**Second Connection Face To Centerline Distance:**

3.750 inches

**Bolt Circle Diameter:**

3.375 inches 2nd end

**Flange Face Design:**

Plain all ends

**Material:**

Rubber butadiene-acrylonitrile class nbr flow control device

**Material Specification:**

Qq-n-228 federal specification single material response stem

**Media For Which Designed:**

Water, salt single response

**Style Designator:**

Err-090

**Furnished Items And Quantity:**

1 lever

**Specification Data:**

81349-mil-v-24332 government specification

**Specification Or Standard:**

B grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-v-24332 spec.