NSN 4820-01-320-2816

Globe Valve - Page 1 of 2

Flow Control Device:

Disk or stem



View Online at https://aerobasegroup.com/nsn/4820-01-320-2816

Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
End Application:
Valves, nonpowered
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Features Provided:
Bonnet packing
Valve Size:
2.500 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
7.000 inches all ends
Face To Face Distance:
8.500 inches
Thickness:
0.880 inches all ends
Bolt Hole Diameter:
0.625 inches all ends
Bolt Circle Diameter:
5.500 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
4.120 inches all ends
Material:
Steel uns j92900 flow control device
Material Specification:

Astm a351 gr cf8m assn standard single material response flow control device

NSN 4820-01-320-2816

Globe Valve - Page 2 of 2



Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 handwheel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0