## NSN 4820-01-321-1790

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-321-1790

Pipe Size Accommodated:
0.750 inches 2nd end
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
425.0 degrees fahrenheit 2nd response
Connection Style:
Socket err-100
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 1st end
Connection Type:
Unthreaded internal pipe 2nd end
Maximum Operating Pressure:
400.0 pounds per square inch 1st response
Opening Pressure Setting:
200.0 pounds per square inch
Outside Diameter:
4.312 inches 1st end
Thickness:
0.688 inches 1st end
Bolt Hole Diameter:
0.562 inches 1st end
Bolt Circle Diameter:
3.188 inches 1st end
Flange Face Design:
Plain 1st end
Material:
Nickel alloy seat
Media For Which Designed:
Air 1st response
Style Designator:
Err-090
Shelf Life:
N/a

## NSN 4820-01-321-1790

Safety Relief Valve - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A046b0