## NSN 4820-01-322-3585

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-322-3585

Bolt Hole Quantity:
8 2nd end
End Application:
Used on 400 ft wagb cg vessels
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.000 inches
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
6.500 inches 1st end
Thickness:
1.188 inches 2nd end
First Connection Face To Centerline Distance:
6.000 inches
Bolt Hole Diameter:
Boil Hole Diameter.
0.750 inches 2nd end
0.750 inches 2nd end
0.750 inches 2nd end Second Connection Face To Centerline Distance:
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter:
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design:
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design: Raised straight all ends
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design: Raised straight all ends  Raised Face Height:
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design: Raised straight all ends  Raised Face Height: 0.062 inches 2nd end
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design: Raised straight all ends Raised Face Height: 0.062 inches 2nd end Raised Face Diameter:
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design: Raised straight all ends Raised Face Height: 0.062 inches 2nd end Raised Face Diameter: 6.187 inches 2nd end
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design: Raised straight all ends  Raised Face Height: 0.062 inches 2nd end  Raised Face Diameter: 6.187 inches 2nd end  Material:
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design: Raised straight all ends Raised Face Height: 0.062 inches 2nd end Raised Face Diameter: 6.187 inches 2nd end Material: Stainless steel seat
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design: Raised straight all ends Raised Face Height: 0.062 inches 2nd end Raised Face Diameter: 6.187 inches 2nd end Material: Stainless steel seat Media For Which Designed:
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design: Raised straight all ends Raised Face Height: 0.062 inches 2nd end Raised Face Diameter: 6.187 inches 2nd end Material: Stainless steel seat Media For Which Designed: Water, fresh single response
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design: Raised straight all ends Raised Face Height: 0.062 inches 2nd end Raised Face Diameter: 6.187 inches 2nd end Material: Stainless steel seat Media For Which Designed: Water, fresh single response Style Designator:
0.750 inches 2nd end  Second Connection Face To Centerline Distance: 5.250 inches  Bolt Circle Diameter: 7.875 inches 2nd end Flange Face Design: Raised straight all ends Raised Face Height: 0.062 inches 2nd end Raised Face Diameter: 6.187 inches 2nd end Material: Stainless steel seat Media For Which Designed: Water, fresh single response  Style Designator: Err-090

## NSN 4820-01-322-3585

Safety Relief Valve - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A046b0