NSN 4820-01-323-5066

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-323-5066

Flow Control Device:

Disk

Disk Loading Method:

Spring

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round all ends

Connection Type:

Flange all ends

Valve Size:

2.000 inches

Adjustable Pressure Range:

+30.0/+34.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

2.375 inches all ends

Thickness:

0.437 inches all ends

First Connection Face To Centerline Distance:

4.750 inches

Second Connection Face To Centerline Distance:

4.750 inches

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Material Specification:

Astmb-61 assn standard single material response body

Media For Which Designed:

Liquid single response

Style Designator:

Err-090

Specification Data:

81349-mil-v-24332 government specification

Specification Or Standard:

B grade

Shelf Life:

N/a



NSN 4820-01-323-5066

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.

