## NSN 4820-01-325-6944

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-325-6944

| Thread Direction:                |          |  |
|----------------------------------|----------|--|
| Right-hand all ends              |          |  |
| Flow Control Device:             |          |  |
| Disk                             |          |  |
| Bonnet Type:                     |          |  |
| Inside screw                     |          |  |
| Bonnet Attachment Method:        |          |  |
| Threaded                         |          |  |
| Connection Style:                |          |  |
| G9 plain, optional en (pipe) 2nd | lend     |  |
| Valve Operation Method:          |          |  |
| Automatic                        |          |  |
| Connection Type:                 |          |  |
| Threaded internal pipe 2nd end   |          |  |
| Adjustable Pressure Range:       |          |  |
| +130.0/+144.0 pounds per squa    | ire inch |  |
| Thread Size:                     |          |  |
| 2.500 inches 2nd end             |          |  |
| Material:                        |          |  |
| Copper alloy 836 body            |          |  |
| Media For Which Designed:        |          |  |
| Air single response              |          |  |
| Style Designator:                |          |  |
| Err-090                          |          |  |
| Thread Series Designator:        |          |  |
| Npt all ends                     |          |  |
| Shelf Life:                      |          |  |
| N/a                              |          |  |
| Unit Of Measure:                 |          |  |
|                                  |          |  |
| Demilitarization:                |          |  |
| No                               |          |  |
| Fiig:                            |          |  |
| A046b0                           |          |  |