NSN 4820-01-330-8118

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-330-8118



Bonnet Type: Inside screw Bonnet Attachment Method: Threaded Bolt Hole Quantity: 4 all ends Maximum Operating Temp: 150.0 degrees fahrenheit single response Valve Operation Method: Automatic Flange Shape: Round with holes all ends Connection Type:

Flow Control Device:

Disk

Flange all ends Valve Size:

3.000 inches

Adjustable Pressure Range:

+23.0/+45.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch single response

Outside Diameter:

6.625 inches all ends

Thickness:

0.938 inches all ends

First Connection Face To Centerline Distance:

5.500 inches

Bolt Hole Diameter:

0.688 inches all ends

Second Connection Face To Centerline Distance:

6.000 inches

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

NSN 4820-01-330-8118

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

