## NSN 4820-01-330-8118

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Type:** 

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-330-8118

Inside screw
Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+23.0/+45.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
6.625 inches all ends
Thickness:
0.938 inches all ends
First Connection Face To Centerline Distance:
5.500 inches
Bolt Hole Diameter:
0.688 inches all ends
Second Connection Face To Centerline Distance:
6.000 inches
Bolt Circle Diameter:
5.500 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

## NSN 4820-01-330-8118

Safety Relief Valve - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0