NSN 4820-01-331-6133

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-331-6133

Bonnet Attachment Method:	
Union	
Bolt Hole Quantity:	
8 all ends	
Maximum Operating Temp:	
150.0 degrees fahrenheit single response	
Valve Operation Method:	
Automatic	
Flange Shape:	
Round with holes all ends	
Connection Type:	
Flange all ends	
Valve Size:	
0.750 inches	
Adjustable Pressure Range:	
+110.0/+160.0 pounds per square inch	
Maximum Operating Pressure:	
400.0 pounds per square inch single response	
Outside Diameter:	
1.050 inches all ends	
Thickness:	
0.688 inches all ends	
First Connection Face To Centerline Distance:	
3.672 inches	
Bolt Hole Diameter:	
0.562 inches all ends	
Second Connection Face To Centerline Distance:	
3.672 inches	
Bolt Circle Diameter:	
3.188 inches all ends	
Flange Face Design:	
Plain all ends	
Material:	
Nickel alloy body	
Media For Which Designed:	
Liquid single response	
Style Designator:	
Err-090	

NSN 4820-01-331-6133

Safety Relief Valve - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0