## NSN 4820-01-332-0195

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bolt Hole Quantity:** 

**Maximum Operating Temp:** 

775.0 degrees fahrenheit single response

Disk

4 all ends



View Online at https://aerobasegroup.com/nsn/4820-01-332-0195

Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Features Provided:
Pressure tight outlet side
Valve Size:
0.500 inches
Adjustable Pressure Range:
+18.0/+32.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Opening Pressure Setting:
30.0 pounds per square inch
Outside Diameter:
3.500 inches all ends
Thickness:
0.438 inches all ends
Bolt Hole Diameter:
0.625 inches all ends
Bolt Circle Diameter:
2.375 inches all ends
Flange Face Design:
Raised straight all ends
Material:
Steel body
Media For Which Designed:
Liquid single response
Style Designator:
Err-090
Specification Data:
81349-mil-v-24332 government specification
Specification Or Standard:
1 type

## NSN 4820-01-332-0195

Safety Relief Valve - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A046b0	

Mil-std (military Standard):

Mil-v-24332 spec.

Shelf Life: