## NSN 4820-01-332-6809

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-332-6809

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
8 1st end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Maximum Operating Pressure:
2500.0 pounds per square inch single response
Opening Pressure Setting:
2000.0 pounds per square inch
Outside Diameter:
6.125 inches 2nd end
Thickness:
2.250 inches 1st end
First Connection Face To Centerline Distance:
6.500 inches
Bolt Hole Diameter:
1.250 inches 1st end
Second Connection Face To Centerline Distance:
5.500 inches
Bolt Circle Diameter:
7.750 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.688 inches 2nd end
Raised Face Diameter:
4.125 inches 1st end

## NSN 4820-01-332-6809

Safety Relief Valve - Page 2 of 2



Material:
Stainless steel stem
Media For Which Designed:
Air 1st response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0