NSN 4820-01-332-7648

Angle Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-332-7648

| Flow Control Device: |
|--|
| Disk |
| Bonnet Type: |
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Bolt Hole Quantity: |
| 4 all ends |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Valve Size: |
| 3.000 inches |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Outside Diameter: |
| 7.500 inches all ends |
| Thickness: |
| 0.688 inches all ends |
| First Connection Face To Centerline Distance: |
| 4.750 inches |
| Bolt Hole Diameter: |
| 0.750 inches all ends |
| Second Connection Face To Centerline Distance: |
| 4.750 inches |
| Bolt Circle Diameter: |
| 6.000 inches all ends |
| Flange Face Design: |
| Raised straight all ends |
| Raised Face Height: |
| 0.062 inches all ends |
| Raised Face Diameter: |
| 5.000 inches all ends |
| Special Features: |
| Stop-check type |
| Material: |
| Steel uns j03002 body |
| Media For Which Designed: |
| Water, fresh single response |

NSN 4820-01-332-7648

Angle Valve - Page 2 of 2



| Style Designator: |
|-------------------|
| Err-090 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A046b0