

View Online at <https://aerobasegroup.com/nsn/4820-01-335-8073>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Threaded

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Facility:

Bracket

Valve Size:

0.500 inches

Maximum Operating Pressure:

300.0 pounds per square inch single response

Criticality Code Justification:

Zzzy

Outside Diameter:

3.750 inches all ends

Face To Face Distance:

6.000 inches

Thickness:

0.500 inches all ends

Bolt Hole Diameter:

0.625 inches all ends

Bolt Circle Diameter:

2.625 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

1.375 inches all ends

Material:

Stainless steel body

Material Specification:

Astm a276 assn standard single material response stem

Style Designator:

Err-090

Furnished Items And Quantity:

1 handwheel

Reference Number Differentiating Characteristics:

Quality control in accordance with navships 0948-045-7010 material identification and control instruction for level 1 items

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0