NSN 4820-01-337-3883

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-337-3883

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+27.0/+33.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
6.625 inches all ends
Thickness:
0.938 inches all ends
First Connection Face To Centerline Distance:
5.750 inches
Bolt Hole Diameter:
0.688 inches all ends
Second Connection Face To Centerline Distance:
5.750 inches
Bolt Circle Diameter:
5.500 inches all ends
Flange Face Design:
Plain all ends
Material:
Copper alloy 922 bodynickel alloy flow control devicenickel alloy seatnickel alloy stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Frr-090

Err-090

NSN 4820-01-337-3883

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0