# NSN 4820-01-337-3889

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-337-3889

# Thread Direction:

Right-hand all ends

# **Flow Control Device:**

Disk

## Bonnet Type:

Inside spring

# **Bonnet Attachment Method:**

Integral

# **Disk Loading Method:**

Spring

## Maximum Operating Temp:

406.0 degrees fahrenheit single response

#### Connection Style:

G46b plain (pipe) 1st endg9 plain, optional en (pipe) 2nd end

#### Valve Operation Method:

Automatic

#### Connection Type:

Threaded external pipe 1st endthreaded internal pipe 2nd end

## Adjustable Pressure Range:

+151.0/+300.0 pounds per square inch

# Thread Size:

0.750 inches 1st end0.500 inches 2nd end

#### Special Features:

Soft seat

## Material:

Copper alloy bodycopper alloy flow control deviceplastic polytrifluoroethylene seatcopper alloy stem

#### Style Designator:

Err-090

#### **Thread Series Designator:**

Npt all ends

#### Furnished Items And Quantity:

1 lever

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A046b0