NSN 4820-01-338-1179

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-338-1179

Body Material:

Steel, federal standard 66, aisi 316/sae 30316

Body Style:

Straight through w/offset

Media For Which Designed:

Air

First End Connection Type:

Threaded external tube

First End Style Designator:

Flared

First End Outside Diameter Tube Accommodated:

0.375 inches

First End Thread Size And Series/type Designator:

0.562-18 unf

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Not identical

Second End Connection Type:

Threaded external tube

Second End Style Designator:

Flared

Second End Outside Diameter Tube Accommodated:

0.250 inches

Second End Thread Size And Series/type Designator:

0.438-20 unf

Second End Thread Class:

3a

Second End Thread Direction:

Right-hand

Seat Material:

Plastic, polychlorotrifluoroethylene

Offset Distance:

0.344 inches

First End Seat Angle In Deg:

37.0

Flow Control Device:

Poppet

Flow Control Device Material:

Steel, federal standard 66, aisi 303/sae 30303

NSN 4820-01-338-1179

Calibrated Flow Valve - Page 2 of 2



End Connection Quantity:

2

Valve Discharge Flow Rate:

1.0 gallons per minute

Regulation Type:

Automatic single stage

Maximum Inlet Pressure Rating:

6000.0 pounds per square inch

Tempurature Rating:

165.0 degrees fahrenheit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A21100