NSN 4820-01-338-2022

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-338-2022 **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Weight **Maximum Operating Temp:** 275.0 degrees fahrenheit 2nd response **Connection Style:** G4 gasket sea (boss) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 2nd end **Maximum Operating Pressure:** 2500.0 pounds per square inch single response **Thread Size:** 0.562 inches all ends Seat Angle: 37.0 degrees 1st end **Opening Pressure Setting:** 280.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.375 inches 2nd end Material: Steel comp 303 body **Material Specification:** Mil-p-25732 military specification single material response seat Media For Which Designed: Ammonia, liquid 4th response **Style Designator:** Err-090 **Thread Series Designator:** Unjf 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 4820-01-338-2022

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-p-25732 spec.