## NSN 4820-01-338-2023



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-338-2023 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** G42 flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends Thready Qty Per Inch (tpi): 12 all ends Adjustable Pressure Range: +10.0/+30.0 pounds per square inch **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 1.312 inches all ends Seat Angle: 37.0 degrees all ends Material: Aluminum alloy 2024 body Media For Which Designed: Air 1st responsefuel/oil, hydrocarbon 2nd responsehelium 3rd responsehydrogen 4th response **Style Designator:** Err-090 **Thread Series Designator:** Un all ends **Furnished Items And Quantity:** 1 deflector cap Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 4820-01-338-2023

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0