NSN 4820-01-338-6419

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-338-6419

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Bolt Hole Quantity:
6 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.500 inches
Adjustable Pressure Range:
+45.0/+49.0 pounds per square inch
Outside Diameter:
6.125 inches all ends
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
6.625 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
5.500 inches
Bolt Circle Diameter:
5.000 inches all ends
Flange Face Design:
Plain all ends
Material:
Copper alloy bodynickel alloy flow control devicenickel alloy seatnickel alloy stem
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090
Shelf Life:
N/a

NSN 4820-01-338-6419

Safety Relief Valve - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A046b0