NSN 4820-01-338-6421

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-338-6421

Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
End Application:
Supply class aoe
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.000 inches
Adjustable Pressure Range:
+57.0/+64.0 pounds per square inch
Outside Diameter:
6.000 inches all ends
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
4.500 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
4.000 inches
Bolt Circle Diameter:
4.750 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090

NSN 4820-01-338-6421

Safety Relief Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0