NSN 4820-01-338-6969



Globe Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-338-6969 Flow Control Device: **Poppet Bonnet Type:** Inside screw **Bonnet Attachment Method: Bolted Maximum Operating Temp:** 400.0 degrees fahrenheit single response **End Application:** No 2 propulsion boiler quick closing valve **Valve Operation Method:** Manual **Connection Type:** Flange all ends Valve Size: 1.250 inches **Maximum Operating Pressure:** 400.0 pounds per square inch single response **Face To Face Distance:** 9.125 inches Flange Face Design: Raised straight all ends **Raised Face Height:** 0.250 inches all ends **Raised Face Diameter:** 2.500 inches all ends Material: Stainless steel bodystainless steel flow control devicestainless steel seatstainless steel stem **Material Specification:** Astm a216 assn standard single material response body Media For Which Designed: Steam 1st responseoil 2nd response

Material:
Stainless steel bodystainless steel flow control devicestainless steel seatstainless steel
Material Specification:
Astm a216 assn standard single material response body
Media For Which Designed:
Steam 1st responseoil 2nd response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
--Demilitarization:

No

NSN 4820-01-338-6969

Globe Valve - Page 2 of 2



Fiig:

A046b0