## NSN 4820-01-338-7425

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-338-7425

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+1055.0/+1160.0 pounds per square inch
Outside Diameter:
7.000 inches 1st end
Thickness:
0.875 inches all ends
Bolt Hole Diameter:
0.875 inches 2nd end
Bolt Circle Diameter:
5.500 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches 2nd end
Raised Face Diameter:
3.562 inches 1st end
Special Features:
1.500 in. 600 lb flange inlet; 2.500 in. 150 lb flange outlet
Material:
Stainless steel stem
Media For Which Designed:
Ctana single vacuums

Steam single response

## NSN 4820-01-338-7425

Safety Relief Valve - Page 2 of 2



:
:

Err-090

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0