NSN 4820-01-339-1530

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-339-1530

Disk
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit 1st response450.0 degrees fahrenheit 2nd response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
4.000 inches
Adjustable Pressure Range:
+53.0/+64.0 pounds per square inch
Maximum Operating Pressure:
285.0 pounds per square inch 1st response185.0 pounds per square inch 2nd response
Outside Diameter:
9.000 inches 1st end9.000 inches 2nd end
Thickness:
1.000 inches 1st end0.938 inches 2nd end
First Connection Face To Centerline Distance:
7.250 inches
Bolt Hole Diameter:
0.875 inches 1st end0.750 inches 2nd end
Second Connection Face To Centerline Distance:
7.000 inches
Bolt Circle Diameter:
9.500 inches 1st end7.500 inches 2nd end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches 1st end1.688 inches 2nd end
Raised Face Diameter:
7.562 inches 1st end5.313 inches 2nd end
Material:
Steel bodysteel comp 630 flow control devicesteel comp 416 stem
Style Designator:
Err-090
Shelf Life:
N/a

NSN 4820-01-339-1530

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0