## NSN 4820-01-340-1256

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Attachment Method:** 

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-340-1256

| Bonnet Attachment Wethou.                      |  |  |
|--|--|--|
| Bolted   |  |  |
| Bolt Hole Quantity:                            |  |  |
| 8 all ends                                     |  |  |
| Maximum Operating Temp:                        |  |  |
| 150.0 degrees fahrenheit single response       |  |  |
| Valve Operation Method:                        |  |  |
| Automatic                                      |  |  |
| Flange Shape:                                  |  |  |
| Round with holes all ends                      |  |  |
| Connection Type:                               |  |  |
| Flange all ends                                |  |  |
| Valve Size:                                    |  |  |
| 4.000 inches                                   |  |  |
| Adjustable Pressure Range:                     |  |  |
| +81.0/+94.0 pounds per square inch             |  |  |
| Maximum Operating Pressure:                    |  |  |
| 150.0 pounds per square inch single response   |  |  |
| Outside Diameter:                              |  |  |
| 9.000 inches 2nd end                           |  |  |
| Thickness:                                     |  |  |
| 0.812 inches 1st end                           |  |  |
| First Connection Face To Centerline Distance:  |  |  |
| 9.094 inches                                   |  |  |
| Bolt Hole Diameter:                            |  |  |
| 0.875 inches 1st end                           |  |  |
| Second Connection Face To Centerline Distance: |  |  |
| 6.532 inches                                   |  |  |
| Bolt Circle Diameter:                          |  |  |
| 9.500 inches 1st end                           |  |  |
| Flange Face Design:                            |  |  |
| Plain all ends                                 |  |  |
| Material:                                      |  |  |
| Nickel alloy flow control device               |  |  |
| Media For Which Designed:                      |  |  |
| Water-oil-gas single response                  |  |  |
| Style Designator:                              |  |  |
| Err-090  |  |  |
|  |  |  |

## NSN 4820-01-340-1256

Safety Relief Valve - Page 2 of 2



|  | Life: |
|--|-------|
|  |       |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0