NSN 4820-01-340-1256

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-340-1256



Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Bolted **Bolt Hole Quantity:** 8 all ends **Maximum Operating Temp:** 150.0 degrees fahrenheit single response Valve Operation Method: Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 4.000 inches Adjustable Pressure Range:

Flow Control Device:

+81.0/+94.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

9.000 inches 2nd end

Thickness:

0.812 inches 1st end

First Connection Face To Centerline Distance:

9.094 inches

Bolt Hole Diameter:

0.875 inches 1st end

Second Connection Face To Centerline Distance:

6.532 inches

Bolt Circle Diameter:

9.500 inches 1st end

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

NSN 4820-01-340-1256

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

