

View Online at <https://aerobasegroup.com/nsn/4820-01-340-6455>

**Flow Control Device:**

Disk

**End Application:**

4820-00-353-7880 direct linear valve, s-3a/b acct

**Special Features:**

Mfg nomenclature pneumatic assembly copilot eject mode selector valve 3.600 in. Lg., 3.440 in. H., 1.000 in. W., 1 corrosion resistant steel shaft per ams 5643 surface passivated per sps 209, 1 corrosion resistant steel pin per qq-w-423 surface passivated per sps 209, 1 corrosion resistant steel sleeve per ams 5643 surface passivated per sp 209, 1 polytetrafluoroethylene backup per ams 3651, 1 corrosion resistant steel fitting per qq-s-764 surface passivated per sps 209, 2 aluminum shear pins per qq-a-208/8 surface red anodized per mil-a-8625, 2 nylon discs per mil-p-17091, 2 corrosion resistant steel rods per qq-s-764 surface passivated per sps 209, 2 aluminum retainers per qq-a-225/6 surface anodized per mil-a-225/6

**Material:**

Aluminum alloy 7075 body

**Material Specification:**

Qq-a-367 federal specification single material response body

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A530b0

**Mil-std (military Standard):**

Mil-a-8625 spec.