AeroBase Group

amphibious / auxiliary.

View Online at https://aerobasegroup.com/nsn/4820-01-341-4273

Body Material: Copper alloy Body Style: Straight thru Stem Material: Nickel copper alloy Media For Which Designed: Water, fresh and water, salt First End Connection Type: Unthreaded internal pipe First End Style Designator: Socket w/brazing ring First End Pipe Size Accommodated: 0.375 inches Second End Relationship With First End: Identical Second End Relationship With First End: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0+60.0 pounds per s		
Body Style: Straight thru Stem Material: Nickel copper alloy Media For Which Designed: Water, fresh and water, salt First End Connection Type: Unthreaded internal pipe First End Connection Type: Outhreaded internal pipe First End Style Designator: Socket wbrazing ring First End Pipe Size Accommodated: 0.375 inches Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class sen (689), spruance class dd (963). Fleet modernization program </th <th>Body Material:</th> <th></th>	Body Material:	
Straight thru Stem Material: Nickel copper alloy Media For Which Designed: Water, fresh and water, salt First End Connection Type: Unthreaded internal pipe First End Style Designator: Socket w/brazing ring First End Pipe Size Accommodated: 0.375 inches Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: 45.0/+60.0 pounds per square inch Regulation Type: Autoratic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class sen (689), spruance class dd (963), Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system ess	Copper alloy	
Stem Material: Nickel copper alloy Media For Which Designed: Water, fresh and water, salt First End Connection Type: Unthreaded internal pipe First End Style Designator: Socket w/brazing ring First End Pipe Size Accommodated: 0.375 inches Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential	Body Style:	
Nickel copper alloy Media For Which Designed: Water, fresh and water, salt First End Connection Type: Unthreaded internal pipe First End Style Designator: Socket w/brazing ring First End Pipe Size Accommodated: 0.375 inches Second End Relationship With First End: Identical Sat Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy Pad Connection Quantity: 2 Outcher Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class sen (688), spruance class dd (963). Fleet modernization program - Fritality Code Justification: Feat Special Features: Weapon system essential	Straight thru	
Media For Which Designed: Water, fresh and water, salt First End Connection Type: Unthreaded internal pipe First End Style Designator: Socket w/brazing ring First End Pipe Size Accommodated: 0.375 inches Second End Relationship With First End: Identical Satt Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class son (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential	Stem Material:	
Water, fresh and water, saltFirst End Connection Type:Unthreaded internal pipeFirst End Style Designator:Socket w/brazing ringFirst End Pipe Size Accommodated:0.375 inchesSecond End Relationship With First End:IdenticalSeat Material:Nickel copper alloyFlow Control Device:Disk, flat, top and bottom guidedFlow Control Device Material:Nickel copper alloyEnd Connection Quantity:2Outlet Pressure Range:+5.0/+60.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmFilter:Not includedEnd Application:Los angeles class son (688), spruance class dd (963). Fleet modernization program -Criticality Code Justification:FeatSpecial Features:Weapon system essentialShelf Life:	Nickel copper alloy	
First End Connection Type: Unthreaded internal pipe First End Style Designator: Socket wbrazing ring First End Pipe Size Accommodated: 0.375 inches Second End Relationship With First End: Identical Set Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class sen (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential	Media For Which Designed:	
Unthreaded internal pipe First End Style Designator: Socket wbrazing ring First End Pipe Size Accommodated: 0.375 inches Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	Water, fresh and water, salt	
First End Style Designator: Socket w/brazing ring First End Pipe Size Accommodated: 0.375 inches Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class sn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	First End Connection Type:	
Socket w/brazing ringFirst End Pipe Size Accommodated:0.375 inchesSecond End Relationship With First End:IdenticalSeat Material:Nickel copper alloyFlow Control Device:Disk, flat, top and bottom guidedFlow Control Device Material:Nickel copper alloyEnd Connection Quantity:2Outlet Pressure Range:+5.0/+60.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:DiaphragmFilter:Not includedEnd Application:FeatSpringRemote Actuation Method:DiaphragmFilter:Not includedEnd Application:FeatSpecial Features:Weapon system essentialShelf Life:	Unthreaded internal pipe	
First End Pipe Size Accommodated: 0.375 inches Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	First End Style Designator:	
0.375 inches Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Diaphragm Filter: Not included End Application: Feat Special Features: Vaepon system essential Shelf Life:	Socket w/brazing ring	
Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class sen (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	First End Pipe Size Accommodated:	
Identical Seat Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class sn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Veapon system essential	0.375 inches	
Seat Material: Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class sn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	Second End Relationship With First End:	
Nickel copper alloy Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Feat Special Features: Weapon system essential Shelf Life:	Identical	
Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	Seat Material:	
Disk, flat, top and bottom guidedFlow Control Device Material:Nickel copper alloyEnd Connection Quantity:2Outlet Pressure Range:+5.0/+60.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmFilter:Not includedEnd Application:Criticality Code Justification:FeatSpecial Features:Weapon system essentialShelf Life:	Nickel copper alloy	
Flow Control Device Material: Nickel copper alloy End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	Flow Control Device:	
Nickel copper alloyEnd Connection Quantity:2Outlet Pressure Range:+5.0/+60.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmFilter:Not includedEnd Application:Criticality Code Justification:FeatSpecial Features:Weapon system essentialShelf Life:	Disk, flat, top and bottom guided	
End Connection Quantity: 2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class son (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	Flow Control Device Material:	
2 Outlet Pressure Range: +5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Veapon system essential Shelf Life:	Nickel copper alloy	
Outlet Pressure Range:+5.0/+60.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmFilter:Not includedEnd Application:Criticality Code Justification:FeatSpecial Features:Weapon system essentialShelf Life:	End Connection Quantity:	
+5.0/+60.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	2	
Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	Outlet Pressure Range:	
Automatic single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	+5.0/+60.0 pounds per square inch	
Valve Loading Method: Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	Regulation Type:	
Spring Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Feat Special Features: Weapon system essential Shelf Life:	Automatic single stage	
Remote Actuation Method: Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	Valve Loading Method:	
Diaphragm Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Feat Special Features: Weapon system essential Shelf Life:	Spring	
Filter: Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	Remote Actuation Method:	
Not included End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Feat Special Features: Weapon system essential Shelf Life:	Diaphragm	
End Application: Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	Filter:	
Los angeles class ssn (688), spruance class dd (963). Fleet modernization program - Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	Not included	
Criticality Code Justification: Feat Special Features: Weapon system essential Shelf Life:	End Application:	
Feat Special Features: Weapon system essential Shelf Life:	Los angeles class ssn (688), spruance class dd (963). Fleet modernization prog	ıram -
Special Features: Weapon system essential Shelf Life:	Criticality Code Justification:	
Weapon system essential Shelf Life:	Feat	
Shelf Life:	Special Features:	
	Weapon system essential	
	Shelf Life:	
N/a	N/a	

Fluid Pressure Regulating Valve - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100