NSN 4820-01-341-4810

Fiig: A046b0



Safety Relief Valve - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/4820-01-341-4810 Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Union **Disk Loading Method:** Spring Renewable Seat Ring Type: Welded **Maximum Operating Temp:** 150.0 degrees fahrenheit 1st response425.0 degrees fahrenheit 2nd response **Connection Style:** Streamlined with one brazing ring (tube) err-100 Valve Operation Method: Automatic **Connection Type:** Unthreaded internal tube all ends Adjustable Pressure Range: +110.0/+160.0 pounds per square inch **Maximum Operating Pressure:** 400.0 pounds per square inch 1st response200.0 pounds per square inch 2nd response **Outside Diameter Tube Accommodated:** 1.500 inches all ends Material: Copper alloy bodynickel alloy flow control devicenickel alloy seatnickel alloy stem Astm-b61 assn standard single material response bodyqq-n-281 federal specification single material response flow control deviceqq-n-281

Material Specification: federal specification single material response seatastm-a-276 assn standard single material response stem Media For Which Designed: Water-oil-gas single response **Style Designator:** Err-090 **Furnished Items And Quantity:** 1 lever Shelf Life: N/a **Unit Of Measure: Demilitarization:** No