

View Online at <https://aerobasegroup.com/nsn/4820-01-342-0568>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Connection Style:

G46a plain (tube) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded external tube all ends

Thready Qty Per Inch (tpi):

12 all ends

Maximum Operating Pressure:

6000.0 pounds per square inch single response

Thread Size:

3.375 inches all ends

Material:

Nickel alloy body and bronze bodyplastic polyamide flow control deviceplastic polyurethane packingsteel comp 316 seatsteel comp 316 stem

Material Specification:

Mil-b-24480 federal specification single material response bodymil-p-17091 federal specification single material response flow control devicemil-r-83397 cl. 2 federal specification single material response packingqq-s-763 federal specification single material response seatqq-s-763 federal specification single material response stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Thread Series Designator:

Un all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-b-24480 spec.