NSN 4820-01-342-6715

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-342-6715

| Flow Control Device: |
|--|
| Disk |
| Bolt Hole Quantity: |
| 4 all ends |
| Maximum Operating Temp: |
| 450.0 degrees fahrenheit single response |
| Valve Operation Method: |
| Automatic |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Mounting Position: |
| Horizontal |
| Valve Size: |
| 2.000 inches |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch 2nd response |
| Outside Diameter: |
| 6.000 inches all ends |
| Face To Face Distance: |
| 8.000 inches |
| Thickness: |
| 0.625 inches all ends |
| Bolt Hole Diameter: |
| 0.750 inches all ends |
| Bolt Circle Diameter: |
| 4.750 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Special Features: |
| Swing check valve |
| Material: |
| Iron body |
| Material Specification: |
| Astm b62 assn standard single material response seat |
| Media For Which Designed: |
| Water-oil-gas 2nd response |
| Style Designator: |
| Straight through flanged ends |
| Shelf Life: |
| N/a |

NSN 4820-01-342-6715

Check Valve - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A530b0