NSN 4820-01-343-3612

Check Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-343-3612

Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
End Application:
Parker-hannifin corp, fluidpower div, model dil-2-274w-mm-yfyf-3 duplex filter
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Bracket
Mounting Position:
Horizontal
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
3.062 inches all ends
Thickness:
1.190 inches all ends
Center To Center Distance:
7.000 inches
Flange Face Design:
Plain all ends
Special Features:
Changeover torque 25 ft/lb at 300.0psi
Material:
Aluminum alloy body
Media For Which Designed:
Hydraulic fluid, petroleum base single response
Furnished Items And Quantity:
1 lever and 2 plugged drain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4820-01-343-3612

Check Valve - Page 2 of 2



Fiig:

A530b0