## NSN 4820-01-344-8999

Safety Relief Valve - Page 1 of 2

A046b0



View Online at https://aerobasegroup.com/nsn/4820-01-344-8999

Pipe Size Accommodated:
1.000 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
150.0 degrees fahrenheit 1st response425.0 degrees fahrenheit 2nd response
Connection Style:
Socket err-100
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Adjustable Pressure Range:
+110.0/+160.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch 1st response200.0 pounds per square inch 2nd response
Special Features:
Incl adjusting ring
Material:
Copper alloy bodynickel alloy flow control devicenickel alloy seatsteel comp 316 stem
Material Specification:
Astm-b61 assn standard single material response bodyastm-b164 assn standard single material response flow control deviceastm-b164
assn standard single material response seat
Media For Which Designed:
Air 1st responsesteam 2nd response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiia·

## NSN 4820-01-344-8999

Safety Relief Valve - Page 2 of 2



Mil-std (military Standard):

Mil-v-22549 spec.