NSN 4820-01-345-1459

Pressure And Temperature Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-345-1459

Body Material:
Steel, qq-s-763, class 304
Body Style:
Single connection angle flow
First End Connection Type:
Threaded internal tube
First End Style Designator:
Plain
Seat Material:
Plastic, tetrafluoroethylene
Flow Control Device:
Poppet
Flow Control Device Material:
Steel, ams 5643
End Connection Quantity:
1
Opening Pressure Setting:
305.0 pounds per square inch
305.0 pounds per square inch Valve Discharge Flow Rate:
Valve Discharge Flow Rate:
Valve Discharge Flow Rate: 8000.0 cubic feet per minute
Valve Discharge Flow Rate: 8000.0 cubic feet per minute Tempurature Adjustability:
Valve Discharge Flow Rate: 8000.0 cubic feet per minute Tempurature Adjustability: Not adjustable
Valve Discharge Flow Rate: 8000.0 cubic feet per minute Tempurature Adjustability: Not adjustable Shelf Life:
Valve Discharge Flow Rate: 8000.0 cubic feet per minute Tempurature Adjustability: Not adjustable Shelf Life: N/a
Valve Discharge Flow Rate: 8000.0 cubic feet per minute Tempurature Adjustability: Not adjustable Shelf Life: N/a Unit Of Measure:
Valve Discharge Flow Rate: 8000.0 cubic feet per minute Tempurature Adjustability: Not adjustable Shelf Life: N/a Unit Of Measure:
Valve Discharge Flow Rate: 8000.0 cubic feet per minute Tempurature Adjustability: Not adjustable Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli
Valve Discharge Flow Rate: 8000.0 cubic feet per minute Tempurature Adjustability: Not adjustable Shelf Life: N/a Unit Of Measure: Demilitarization:
Valve Discharge Flow Rate: 8000.0 cubic feet per minute Tempurature Adjustability: Not adjustable Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: