

View Online at <https://aerobasegroup.com/nsn/4820-01-345-3822>

**Flow Control Device:**

Disk

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

214.0 gallons per minute

**Bolt Hole Quantity:**

6 all ends

**Maximum Operating Temp:**

150.0 degrees fahrenheit single response

**Valve Operation Method:**

Automatic

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Valve Size:**

2.000 inches

**Adjustable Pressure Range:**

+30.0 to 34.0 pounds per square inch

**Maximum Operating Pressure:**

150.0 pounds per square inch single response

**Outside Diameter:**

5.562 inches all ends

**Thickness:**

0.438 inches all ends

**First Connection Face To Centerline Distance:**

5.500 inches

**Bolt Hole Diameter:**

0.562 inches all ends

**Second Connection Face To Centerline Distance:**

4.500 inches

**Bolt Circle Diameter:**

4.438 inches all ends

**Flange Face Design:**

Plain all ends

**Extra Long Reference Number:**

46h0-205/m5 cds 653 nmp-1102 opt.A

**Special Features:**

Valve size 2 in. Inlet by 3 in. Outlet

**Material:**

Copper alloy body

**Media For Which Designed:**

Water, fresh single response

**Style Designator:**

C1a angle flanged ends

**Furnished Items And Quantity:**

1 lever

**Reference Number Differentiating Characteristics:**

Elrn

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0