

View Online at <https://aerobasegroup.com/nsn/4820-01-345-3822>

Flow Control Device:

Disk

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

214.0 gallons per minute

Bolt Hole Quantity:

6 all ends

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.000 inches

Adjustable Pressure Range:

+30.0 to 34.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

5.562 inches all ends

Thickness:

0.438 inches all ends

First Connection Face To Centerline Distance:

5.500 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

4.500 inches

Bolt Circle Diameter:

4.438 inches all ends

Flange Face Design:

Plain all ends

Extra Long Reference Number:

46h0-205/m5 cds 653 nmp-1102 opt.A

Special Features:

Valve size 2 in. Inlet by 3 in. Outlet

Material:

Copper alloy body

Media For Which Designed:

Water, fresh single response

Style Designator:

C1a angle flanged ends

Furnished Items And Quantity:

1 lever

Reference Number Differentiating Characteristics:

Elrn

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0