NSN 4820-01-345-5554

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-345-5554

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+100.0/+111.0 pounds per square inch
Outside Diameter:
7.500 inches all ends
Thickness:
0.940 inches all ends
First Connection Face To Centerline Distance:
6.375 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
6.125 inches
Bolt Circle Diameter:
3.000 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
5.000 inches all ends
Material:
Steel bodystainless steel flow control devicestainless steel stem
Style Designator:
Err-090

NSN 4820-01-345-5554

Safety Relief Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0