

View Online at <https://aerobasegroup.com/nsn/4820-01-346-4124>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Needle

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

G43 external seat for gasket seal (boss) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded external boss all ends

Mounting Facility:

Panel

Thready Qty Per Inch (tpi):

20 all ends

Maximum Operating Pressure:

5000.0 pounds per square inch single response

Thread Size:

0.438 inches all ends

Seat Angle:

37.0 degrees all ends

Special Features:

Aluminum alloy handle

Material:

Stainless steel body stainless steel flow control device rubber butadiene-acrylonitrile class nbr packing stainless steel stem

Material Specification:

Mil-r-7362 military specification single material response packing

Media For Which Designed:

Oil, lubricating, diester base single response

Style Designator:

Err-090

Thread Series Designator:

Unj all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-r-7362 spec.