

View Online at <https://aerobasegroup.com/nsn/4820-01-347-0689>

Pipe Size Accommodated:

0.250 inches 3rd end

Thread Class:

2a 1st end

Thread Direction:

Right-hand all ends

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Maximum Operating Temp:

450.0 degrees fahrenheit single response

Minimum Operating Temp:

-65.0 degrees fahrenheit

End Application:

4920-01-211-2815 regulator test set, av-8a/c acft

Connection Style:

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Mounting Facility:

Panel

Maximum Operating Pressure:

500.0 pounds per square inch single response

Thread Size:

0.250 inches all ends

Special Features:

Tremovable handle measures 1.910 in. Across top, panel mtg nut included, panel mtg thickness 0.190 in. Max., from back of panel to bottom of part 1.270 in., from top of handle to centerline of port 3.280 in. Max., 24 threads per inch

Material:

Plastic polyamide flow control device

Style Designator:

Err-090

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0