## NSN 4820-01-348-4263

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-348-4263

Flow Control Device:
Disk
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
43.0 degrees fahrenheit 2nd response
Width:
3.250 inches all ends
Length:
4.000 inches all ends
Valve Operation Method:
Automatic
Flange Shape:
Rectangular with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Bracket
Mounting Position:
Horizontal
Valve Size:
2.500 inches
Maximum Operating Pressure:
1.0 pounds per square inch single response
Face To Face Distance:
1.420 inches
Thickness:
0.062 inches all ends
Bolt Hole Diameter:
0.174 inches all ends
Center To Center Distance Between Bolt Holes Along Length:
2.625 inches all ends
Center To Center Distance Between Bolt Holes Along Width:
2.375 inches all ends
Flange Face Design:
Plain all ends
Material:
Stainless steel seat
Material Specification:
Qq-a-596 federal specification 1st material response flow control device or qq-a-275/6 federal specification 2nd material response flow
control device
Media For Which Designed:
Water-oil-gas single response

## NSN 4820-01-348-4263

Check Valve - Page 2 of 2

Mil-s-5059 spec.



Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Style Designator:
Straight through flanged ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A530b0
Mil-std (military Standard):